

RDR Tec is creating radar for tomorrows technology in the FireScout unmanned helicopter



Sense And Avoid (SAA)

For the past two years RDR Tec under NAVAIR SAA SBIRs has developed radar SENSE concepts to meet Fire Scout SAA requirements. The concept uses advanced AESA technology and proprietary signal processing to provide actionable collision warning information with over 30 sec lead time for a 1 sq. meter RCS non-cooperative aircraft travelling at speeds from 0 to 400 Kts. This includes 2 Hz track update rate and angle accuracies of one degree with false alarm times greater than 1 hour.

Automated Ship and Small Craft Classification Tools for ISAR

RDR Tec is working closely with SAIC in developing innovative ISAR classification tools. This includes image processing and image selection algorithms. Feature extraction algorithms of

individual images include length estimation and determination of whether the image is a profile or plan view. Depending on the view, additional feature such as height, superstructure and upright size/shape/location as well as width and bow and stern shape are estimated. Over multiple frames these feature estimates are accumulated. Estimates of vessels natural roll period and weight as well as the presence and location of rotating antennas are extracted. Ship feature classification will be extended to include AIS consistency check capabilities. The AIS code obtained is checked against the features that are consistent with the vessel that is assigned the AIS code. In addition, is the position reports consistent with where the vessel would most likely be located (i.e., large vessel in shallow water or away from shipping lanes).

Adaptive Active Electronically Scanned Arrays (AESA)>

RDRTec Inc. is developing adaptive multi-channel phased array manifold concepts that reconfigures by radar mode for optimum performance. The emphasis will be on candidate multi-mode X or C-band radars with phased arrays that support modes with both high and low bandwidth requirements. High bandwidth modes include Synthetic Aperture Radar (SAR), Inverse Synthetic Aperture Radar (ISAR), and High Range Resolution (HRR). Relatively low bandwidth modes include Ground Moving Target Indicator (GMTI), Maritime Moving Target Indicator (MMTI), Air-to-Air (AA) and Sense and Avoid (SAA) modes. The target initial transition platform is the Fire Scout but the lessons learned may impact other future Navy ISR radars.